

# uniq tablet



Durable 9,7" industrial tablet



A wide range of uses

- energetics
- logistics
- industry
- health care

[www.elcomitsolutions.eu](http://www.elcomitsolutions.eu)





# Uniq Tablet

## Specifications

Display	
Display	9,7"
Resolution	1024 x 768 pixels
Aspect ratio	4:3
Luminance	300 cd/m <sup>2</sup>
Contrast Ratio	600:1
Backlight Unit	LED
Horizontal Viewing Angle	178°
Vertical Viewing Angle	178°
Touch screen	Projective capacitive Dual Touch
I/O port	
USB	2 x USB (USB-A, Mini USB)
SIM Card Slot	Yes
Microphone	Built-in
Stereo Speakers (2x0,5W)	Built-in
Dock Connector	Yes
Headphone Output	Yes
DC in	12V/2A
CPU	
CPU	Intel Atom Z670
Memory	2GB RAM, DDR2
Storage	SSD 16GB (32GB, 64GB optional)
Cooling System	Fanless (passive)
Communications	
WiFi 802.11b/g/n	Yes
3G Module	Yes (optional)
Bluetooth	Yes (optional)
G-sensor	Yes
L-sensor	Yes
Camera	1.3 Mega Pixels
Power Parameters	
Powersupply	12 V
Power Consumption	24 W
Rechargeable Battery	4000 mAh/7,4 V
AC Adapter	Yes
Mounting	
Mounting type	Table and Wall Stand, HAND STRIPE, VESA 75 (optional)
Dimensions (WxHxD)	209,4 x 282,1 x 30,1 mm
Weight	1,2 kg
Operation	
Operating Temperature	0°C to 35°C
Storage Temperature	-10°C to 70°C
Relative Humidity	5% - 95%, Non-Condensing
IP Level	IP54

The Uniq Tablet is a mobile touchscreen computer ideal for those who usually work under demanding conditions, whether exterior or interior.

It is suitable for handling in a dusty environment or where there is the possibility of contact with water. The Uniq Tablet is also resistant to falling from height of 80 cm.

**The Uniq Tablet is a multimedia device that enables simple and effective communication.** The Uniq Tablet has a built-in camera, microphone and speakers, which allow you to make calls, transmit images or even take pictures.

**The Uniq Tablet also supports a 3G connection to the Internet.**

Communication with applications, software and others devices needed for diagnosing or controlling is very simple and available anywhere.

The Uniq Tablet control is comfortable thanks to the double-touch capacitive display. The G-sensor allows automatic rotation of the image.

- The L-sensor supports automatic customization of the surrounding light conditions.
- OS Windows 7/8



ELCOM, spoločnosť s ručením obmedzeným, Prešov  
Jesenná 2695/26, 080 01 Prešov, Slovakia

Tel.: 00421 51 74 64 111 | E-mail: [elcom@elcom.eu](mailto:elcom@elcom.eu)  
[www.elcomitsolutions.eu](http://www.elcomitsolutions.eu)

Elcom reserves the right to make changes and improvements to any of the products described in this document without prior notice. The photos in this document may not show the actual layout. Specifications are subject to change without notice.

